Seat Belts for Forklift

Forklift Seat Belts - Described in the Regulation guidelines are the use of seatbelts and operator restraints on lift trucks. It says that the liability falls on the employers' to make sure that each machine, piece of equipment and tool is utilized properly used according to the directions of the maker.

In regards to their inspection, fabrication, use, design and maintenance Rough Terrain forklifts ought to satisfy the guidelines of ANSI Standard ASME B56.6-1992.

Side boom tractors and mobile machinery together with a Rollover Protective Structure, or ROPS for short, should have seat belts that meet the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile machinery includes seat belts required by law, the operator and subsequent passengers must make sure they make use of the belts each time the vehicle is in motion or engaged in operation since this could cause the equipment to become unsteady and thus, not safe.

When a seat belt or various operator restraint is needed on a forklift.

The seat belt requirements while working a forklift depend on various factors. Whether the forklift is equipped with a Rollover Protective Structure, the type of lift truck itself and the year the forklift was actually made all add to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

Referring to a driver restraint device, system or enclosure, ANSI Standard ASME B56.1-1993 regarding powered industrial trucks, is designed to help the operator in lowering the risk of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device can comprise a seat belt, although a seat belt is not essentially a part of such machine or system.